

SFP-31-D Series



1.25Gbps Industrial Ethernet SFP (Small Form-factor Pluggable) Transceiver with SFF-8472 DMI

Features

- Data Rate 1.25Gbps
- Single +3.3V power supply
- RoHS compliance
- Low power dissipation
- Class I laser product
- Low EMI and excellent ESD protection
- Industrial temperature (-40 to 85°C)
- SFF-8472 Digital Diagnostic Monitoring Interface compliant

Description

Connection Technology Systems SFP (Small Form-factor Pluggable) transceiver complies with IEEE 802.3z 1000Base-X standard and also provides DMI (Diagnostic Monitoring Interface) function, which allows real-time access to device operating parameters such as transceiver temperature, laser bias current, transmitted optical power, received optical power and transceiver supply voltage.

SFP can be mixed and matched on a given switch to maximize flexibility. However, the connection and associated port at the remote end must match the chosen SFP connection type. CTS SFP transceiver can be used in those CTS Switches and Converter which support SFP modules.

Order Information

SFP-31-D

Model	Fiber Port					Operating Temperature
	Speed	Type	Connector	Distance	Wavelength	
SFP-31FC-D	1000Mbps	MM	LC	550M	850nm	-40°C ~ 85°C
SFP-31FC-(MM-02)-D	1000Mbps	MM	LC	2KM	1310nm	-40°C ~ 85°C
SFP-31FC(SM-10/20)-D	1000Mbps	SM	LC	10/20KM	1310/1310nm	-40°C ~ 85°C
SFP-31W2A(SM-10/20)-D	1000Mbps	WDM	LC	10/20KM	TX: 1310/1310nm	-40°C ~ 85°C
					RX: 1550/1550nm	
SFP-31W2B(SM-10/20)-D	1000Mbps	WDM	LC	10/20KM	TX: 1550/1550nm	-40°C ~ 85°C
					RX: 1310/1310nm	